

## 4MP Smart Dual Light Entry AI Fixed-Focal IPC



- 4MP 1/2.8" CMOS Sensor
- Support H.264+, H.265+
- IR Light: 30 m, White Light: 30m
- 2.8mm fixed lens (3.6mm optional)
- 12 VDC/PoE power supply
- IP67 protection

Camera	
Image Sensor	1/2.8" CMOS
Max. Resolution	4MP
Scanning System	Progressive
Electronic Shutter Speed	Auto(1/25s ~ 1/1000)
Min. Illumination	0.01 Lux @F2.0
S/N Ratio	> 56 dB
Illumination Distance	IR Light: 30 m, White Light: 30m
Illuminator Control	Auto; Manual
Lens	
Lens Type	Fixed-Focal
Focal Length	2.8mm/3.6mm
Max. Aperture	F2.0
Iris Type	Auto
Intelligence	
Human Detection	Support
Smart Motion Detection	Support(based on Human Detection)
Perimeter Protection	NA
Face Detection	NA
Object Detection	NA
People Counting	NA
Heat Map	NA
AI Search	NA
Video	
Compression	H.264H; H.264M; H.264B; H.265
Video Frame Rate	Main Stream: 4MP (1 fps~25/30 fps)
	Sub Stream: D1 (1 fps~25/30 fps)
Stream Capability	2 Streams
Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 1792Kbps~4Mbps

## Entry AI Series | IPC-E1410C-S2-L

	H.265: 1792Kbps~4Mbps
Day/Night	Color/B/W
BLC	Yes
HLC	Yes
WDR	DWDR
White Balance	Yes
Gain Control	Auto/Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 Areas, rectangular)
Image Rotation	0°/180°
Mirror	Yes
Privacy Masking	4 Areas
<b>Audio</b>	
Built-in Mic	NA (optional)
<b>Alarm</b>	
Alarm Event	Disconnection; IP Conflict; No SD Card; Capacity Warning; SD Card Error
<b>Network</b>	
Network	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network Protocol	TCP/IP;UDP;HTTP;DHCP;DDNS;FTP;UPNP
Interoperability	ONVIF; CGI
Storage	SD Card (Optional)
Browser	IE: IE8 and later
Management Software	PC Software(SVMS)
Mobile Client	IOS; Android
<b>Power</b>	
Power Supply	12V DC (±30%)/PoE (802.3af)
Power Consumption	Max. 3W
<b>Environment</b>	
Operating Conditions	-30°C to +60°C (-22°F to +140°F)/Less than 95% RH
Storage Conditions	-40°C to +60°C (-40°F to +140°F)
Protection Grade	IP67
<b>Structure</b>	
Casing	Inner core+Cover: Metal; Ring Cover:Plastic
Dimensions	Φ110mm×97mm
Net Weight	430g